

1102 B型系列

CPD轮轮径× 轮宽100 x 32mm


EAN

KS-11020400292011

活动式脚轮，焊接钢板架—孔距90x60
表面喷蓝漆，底板式安装装置
铸铁制轮芯，高品质聚丙烯轮面
本色，轮子轴承—精密滚珠。

轮面：高品质聚丙烯制成

产品说明仅供参考一切以实体产品为主



图片可能与原始产品有所落差


产品详细规格

☒ 公制 ☐ 英制	
轮径	100mm
轮宽	32mm
轮子轴承	搭配滚珠轴承的轮子
底板规格	120 x 90mm
底板孔距	90X60mm
底板孔径	12mm
偏心距	40.5mm
旋转干涉	186mm
总高	147mm
旋转半径	93mm
硬度	65±5° Shore D
荷重(动态)	200kgs
荷重(静态)	300kgs
温度	-10°C to +60°C
脚架样式	活动
不锈钢	否
导电	否
抗静电	否
脚轮重量	2.25kgs
测试标准	ISO22883


优势简览

滚动顺畅	● ● ● ● ●
静音表现	● ● ● ○ ○
保护地板	● ● ● ○ ○

脚轮外观尺寸2D图档



底板外观尺寸2D图档



图纸仅供参考一切以实体产品为主

* 对公制和英制规格之间有任何偏差疑虑，请以公制规格为主。

SELECT a.mblan,a.mb006cn,a.mb006en,a.mb006vn, d.op1name,d.op1namecn,d.op1nameen,d.op1namevn,a.mb000,a.mb002,a.mb019,a.mb019a,a .mb019b, a.mb102,a.mb00y,a.mblan,a.mb022a,a.mb023a,a.mb0tw,a.mb0ks,a.mb0yj,a.mb0vn, a.mb021a,a.mb006,a.mb102 ,a.mb203,a.mb018a ,c.mb00xa1,c.mb00ya1,c.mb018a1,b.se002tw,b.se002cn,b.se002en,b.se002vn FROM invmb99 as a left join series as b on a.mb002= b.se001 left join invmb99tra as c on a.mb000=c.mb000k left join palop1 d on mb010c=op1no left join invmb99pic as e on a.mb000=e.mb000 where trim(mblan)='2' and a.mb0page ='Y' and trim(mb010c)='12022904151300' and substring(a.mb002,1,4)='1102' and trim(a.mb000)<>'1102-CN-KS2025010301' and trim(mb018a1)> ='145.5' and trim(mb018a1)<='148.5'and trim(mb031)='a' and trim(mb033a3)='90X60'



原文

提供更好的翻译建议
