1115-1 Economy -1 Spring Wheel Series

PU (red round) Wheel Diameter x Wheel Width 125 x 45mm


EAN

KS-11150501331151B

Rigid Spring-loaded Caster with Welded Caster Fork
Blue painted finish, Mounting Type - Top Plate, Bolt Hole Spacing 105 x 78.5
Cast Iron core with High Quality Polyurethane Wheel Tread
White glue finish, Ball Bearings

Wheel tread: Made of high-quality polyurethane Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Metric ○ Imperial

Wheel Diameter 125mm
Wheel Width 45mm

Wheel Bearing Wheels With Ball Bearings

Plate Size 140 x 110mm

Bolt Hole Spacing 105 x 78.5mm

Plate Hole 25 x 13.5mm

Overall Height 185mm

Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 350kgs

Load Capacity (Static) 525kgs

Temperature -20°C to +70°C

Fork Type Rigid Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 3.79kgs

Standard ISO22883


Advantages at a glance


Rolling Resistance

Operating Noise • • •


Floor Surface Preservation • • • • ○

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.