



1123 Shopping Cart Casters Series

Climbing Wheel (Black Gray) Wheel Diameter × Wheel Width 125×22mm


EAN

KS-11230500131483A

Rigid Casters, Threaded Stem installation, thread type M12x40. Rust-proof, Corrosion resistant, Attractive appearance, Economical, and rotates smoothly. High-Quality Impact-Resistant Polypropylene Wheel Center, High Quality Polyurethane Wheel Tread. Dark gray, Bearing—Ball Bearings.

Wheel Tread: Hhigh-Quality Polyurethane  
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

<input checked="" type="radio"/> Metric <input type="radio"/> Imperial	
Wheel Diameter	125mm
Wheel Width	22mm
Wheel Bearing	
Threaded Stem	M12
Threaded Length	40mm
Offset	43mm
Overall Height	150mm
Hardness Of Tread	82±5° Shore A
Load Capacity (Dynamic)	50kgs
Load Capacity (Static)	75kgs
Temperature	-20°C to +60°C
Fork Type	Rigid Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.61kgs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.