1142 Kingpinless Caster (B Type) Series

Dersheng Casters Keep Rolling

QPU (brown round) Wheel Diameter x Wheel Width 200 x 50mm


EAN

KS-11420800534131

Casters with front brake and With locking system, Welded Caster Fork Blue-painted finish, Mounting Type - Top Plate, 110x75 Bolt Hole Spacing Cast Iron Wheel Center, High Quality Polyurethane Wheel Tread, Cast Iron brown Bearings—Ball Bearings with special Anti-thread wheel cover

Wheel tread: Made of high-quality polyurethane Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Metric ○ Imperial

Wheel Diameter 200mm
Wheel Width 050mm

Wheel Bearing Wheels With Ball Bearings

Plate Size 140 x 110mm **Bolt Hole Spacing** 110x75mm Plate Hole 13 x 22mm Offset 47mm 342mm Swivel Interference Overall Height 248mm **Swivel Radius** 171mm Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 670kgs

Load Capacity (Static) 1005kgs

Temperature -20°C to +70°C

Fork Type Swivel Caster With Front Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 6.33kgs

Standard ISO22883

Advantages at a glance


Rolling Resistance


Operating Noise

•

Floor Surface Preservation • • • • •

Dimensions





^{*} For any deviation between metric and imperial spec, please refer to the metric spec.