1146 46 Ascendant Series Caster Series(All Plastic)

Dersheng Casters Keep Rolling

Resolute Rubber wheel (all black) Wheel Diameter x Wheel Width 75 x 14mm

EAN

KS-11460300451043

Rigid Caster with 42.5 x 42.5 mm angled hole Fork Black Fork with reinforced Polypropylene Rustproof and Corrosion resistant, with Smooth rotation for Light and Medium Duty trolleys High-Quality Impact-Resistant Polypropylene Wheel Center with High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread Black, Bearing: Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR) Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

Wheel Width

● Imperial ○ Metric

3 " Wheel Diameter 2-7/16"

Wheel Bearing Wheels With Ball Bearings

2-7/16 " x 2-7/16 " Plate Size **Bolt Hole Spacing** 1-11/16"x1-11/16" 3/8 " x 1/4 " Plate Hole

3-5/8 " Overall Height

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 198lbs Load Capacity (Static) 298lbs

Temperature -4°F to +140°F Fork Type Rigid Caster Stainless N/A **Electrical Conductivity** N/A Anti-Static N/A Weight 0.7lbs Standard ISO22881


Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.