


Resolute Rubber wheel (white dark gray) Wheel Diameter x Wheel Width 75 x 14mm


EAN

KS-11460300454023



Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



☒ Imperial ☐ Metric	
Wheel Diameter	3 "
Wheel Width	2-7/16 "
Wheel Bearing	Wheels With Ball Bearings
Plate Size	1-11/16 " x 1-11/16 "
Bolt Hole Spacing	1-1/4"x1-1/4"
Plate Hole	1/4 "
Offset	15/16 "
Swivel Interference	7-1/16 "
Overall Height	3-5/8 "
Swivel Radius	3-9/16 "
Hardness Of Tread	72±5° Shore A
Load Capacity (Dynamic)	198lbs
Load Capacity (Static)	298lbs
Temperature	-4°F to +140°F
Fork Type	Swivel Caster With Total Brake
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.7lbs
Standard	ISO22881

Rolling Resistance ● ● ● ● ●

Operating Noise ● ● ● ● ●

Floor Surface Preservation ● ● ● ● ●

Technical drawing of the 6000 series pressure washer, showing two views:

- Front View (Left):** Shows the circular spray lance assembly with a diameter of $\varnothing 75$. The height from the base to the top of the lance handle is 91. The width of the lance head is 23.
- Side View (Right):** Shows the profile of the device with a total width of 60. The distance from the centerline to each side edge is 14.

© Copyright 2025 DershengInternational www.dersheng.com