1146 46 Ascendant Series Caster Series(All Plastic)

Resolute Rubber wheel (all black) Wheel Diameter x Wheel Width 75 x 14mm

EAN

KS-11460300454123

Short Total Brake Casters, 42.5x42.5mm angled perforated Top Plate

Black Casters made of polypropylene reinforced material

Rust-proof, Corrosion resistant, Attractive appearance, Economical, and allows for smooth rotation

High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread

Black, Bearing—Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 3 "

Wheel Width 2-7/16 "

Wheel Bearing Wheels With Ball Bearings

Plate Size 2-7/16 " x 2-7/16 " Bolt Hole Spacing 1-11/16"x1-11/16"

Plate Hole 3/8 " x 1/4 "

Offset 15/16 "

Swivel Interference 7-1/16 "

Overall Height 3-5/8 "

Swivel Radius 3-9/16 "

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 198lbs

Load Capacity (Static) 298lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Total Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.8lbs

Standard ISO22881

Advantages at a glance

Rolling Resistance


• • • •


Operating Noise

. . . .


Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.