# 1146 46 Ascendant Series Caster Series(All Plastic)

Dersheng Casters Keep Rolling

Resolute Rubber wheel (all black) Wheel Diameter x Wheel Width 75 x 14mm

EAN

KS-11460300456193

Short Total Brake Casters, Threaded Stem M12x25
Black Caster Fork made of polypropylene reinforced material

Rust-proof, Corrosion resistant, Attractive appearance, Economical, and allows for smooth rotation

High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread

Black, Bearing—Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

#### Technical Data

● Metric ○ Imperial

Wheel Diameter 75mm
Wheel Width 60mm

Wheel Bearing Wheels With Ball Bearings

Threaded Stem M12

Threaded Length 25mm

Offset 23mm

Swivel Interference 179mm

Overall Height 84mm

Swivel Radius 89.5mm

Hardness Of Tread 72±5° Sho

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 90kgs

Load Capacity (Static) 135kgs

Temperature -20°C to +60°C

Fork Type Swivel Caster With Total Brake

ISO22881

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.32kgs

Standard


#### Advantages at a glance

Rolling Resistance • • • •


Operating Noise • • • •

Floor Surface Preservation • • • • •

### Dimensions



## Mounting



<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.