1146 46 Ascendant Series Caster Series(All Plastic)

Dersheng Casters Keep Rolling

Resolute Rubber wheel (white dark gray) Wheel Diameter x Wheel Width 75x 14mm

EAN

KS-11460391454013

Short Total Brake Casters, 42.5x42.5mm angled hole Top Plate
White legs made of polyamide reinforced material
Rust-proof, Corrosion resistant, Smooth rotation, suitable for low and medium-duty trolleys
High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced
Polypropylene Rubber (TPR) Wheel Tread
White and dark gray, Bearing - Ball Bearings

Wheels With Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

Wheel Bearing

● Imperial ○ Metric

Wheel Diameter 3 "

Wheel Width 2-7/16 "

Plate Size 2-7/16 " x 2-7/16 "

Bolt Hole Spacing 1-11/16"x1-11/16"

Plate Hole 3/8 " x 1/4 "

Plate Hole 3/8 " x 1/4 "

Offset 15/16 "

Swivel Interference 5-3/8 "

Overall Height 3-9/16 "

Swivel Radius 2-11/16 "

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 198lbs

Load Capacity (Static) 298lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Total Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.7lbs

Standard ISO22881


Advantages at a glance

Rolling Resistance


Operating Noise • • • • •

Floor Surface Preservation • • • • •

Dimensions



Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.