1146 46 Ascendant Series Caster Series(All Plastic)

Resolute Rubber wheel (white dark gray) Wheel Diameter x Wheel Width 75x 14mm

EAN

KS-11460391459213

Portable Casters, Single Bolthole polyamide legs—hollow Ø10.5

White legs are made of polyamide reinforcement.

Rust-proof, Corrosion resistant, Attractive appearance, Economical, and allows for Smooth rotation.


High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread.

Dark gray, Bearing—Ball Bearings.

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

Offset

● Imperial ○ Metric

3 " Wheel Diameter

2-7/16" Wheel Width

Wheel Bearing Wheels With Ball Bearings

3/8 "

5-3/8 "

3-1/4 "

298lbs

2-11/16 "

72±5° Shore A

-4°F to +140°F

Single Bolt HoleCentre Hole

15/16 "

Swivel Interference

Overall Height

Swivel Radius

Hardness Of Tread

198lbs

Load Capacity (Dynamic)

Load Capacity (Static)

Temperature

Swivel Caster

Fork Type

Stainless

N/A

Electrical Conductivity

Anti-Static

Weight

Standard

N/A

N/A

0.5lbs

ISO22881


Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.