



1146 46 Ascendant Series Caster Series(All Plastic)

Resolute Rubber wheel (window gray dark gray) Wheel Diameter x Wheel Width 100 x 18mm


EAN

KS-11460400457133

Rigid Casters, mortise-and-tenon Stamping Fork—Ø28x30L  
Window gray legs are made of polyamide reinforced material  
Rust-proof, Corrosion resistant, Attractive appearance, Economical, and allows for Smooth rotation  
High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread  
Dark gray, Bearing—Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)  
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                           |
| Wheel Diameter                                                         | 4 "                       |
| Wheel Width                                                            | 3-3/8 "                   |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Stem Diameter                                                          | 1-1/8 "                   |
| Stem Length                                                            | 1-3/16 "                  |
| Overall Height                                                         | 4-13/16 "                 |
| Hardness Of Tread                                                      | 72±5° Shore A             |
| Load Capacity (Dynamic)                                                | 220lbs                    |
| Load Capacity (Static)                                                 | 331lbs                    |
| Temperature                                                            | -4°F to +140°F            |
| Fork Type                                                              | Rigid Caster              |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 1.7lbs                    |
| Standard                                                               | ISO22881                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | • • • • • |
| Operating Noise            | • • • • • |
| Floor Surface Preservation | • • • • • |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.