1146 46 Ascendant Series Caster Series(All Plastic)



Resolute Rubber wheel (white dark gray) Wheel Diameter x Wheel Width 125 x 18mm

EAN


KS-11460500455523

Swivel Casters, Threaded Stem M12x17 White legs made of polyamide reinforced material Rust-proof, Corrosion resistant, Attractive appearance, Economical, and allows for smooth rotation High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread Dark gray, Bearing—Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Metric ○ Imperi	al
Wheel Diameter	

125mm Wheel Width 85.5mm

Wheel Bearing Wheels With Ball Bearings

Threaded Stem M12 Threaded Length 17mm Offset 40mm Swivel Interference 220mm Overall Height 141mm **Swivel Radius** 110mm Hardness Of Tread

72±5° Shore A

Load Capacity (Dynamic) 110kgs Load Capacity (Static) 165kgs

-20°C to +60°C Temperature

Fork Type **Swivel Caster**

Stainless N/A **Electrical Conductivity** N/A Anti-Static N/A Weight 0.64kgs

Standard


Advantages at a glance

Rolling Resistance


Operating Noise

Floor Surface Preservation • • • • •

Dimensions



Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.

ISO22883