## 1146 46 Ascendant Series Caster Series(All Plastic)

Resolute Rubber wheel (white dark gray - large cover version) Wheel Diameter x Wheel Width 125 x 18

EAN


KS-11460500455743

Swivel Casters, Threaded Stem M16x30 White legs made of polyamide reinforced material Rust-proof, Corrosion resistant, Attractive appearance, Economical, and rotates smoothly High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread Dark gray, Bearing—Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

## **Technical Data**

Metric O Imperial

Wheel Diameter 125mm Wheel Width 85.5mm

Wheel Bearing Wheels With Ball Bearings

**Threaded Stem** M16 Threaded Length 30mm Offset 40mm **Swivel Interference** 220mm Overall Height 141mm **Swivel Radius** 110mm Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 110kgs Load Capacity (Static) 165kgs

-20°C to +60°C Temperature


Fork Type **Swivel Caster** 

Stainless N/A **Electrical Conductivity** N/A Anti-Static N/A Weight 0.68kgs Standard ISO22883


## Advantages at a glance

Rolling Resistance **Operating Noise** Floor Surface Preservation • • • • •

## **Dimensions**



Mounting



<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.