



1147 Universal (Single) Spring Wheel Series

QPU (Brown round) Wheel Diameter × Wheel Width 150 x 42mm


EAN

KS-11470600534211

Spring-loaded Caster with front brake, Welded Caster Fork Blue painted finish, Mounting Type - Top Plate, 110x75 Bolt Hole Spacing Cast Iron core, High Quality Polyurethane Wheel Tread Cast Iron brown, Bearing – Ball Bearings

Wheel tread: Made of high-quality polyurethane
Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

☒ Metric ☐ Imperial

Wheel Diameter	150mm
Wheel Width	42mm
Wheel Bearing	Wheels With Ball Bearings
Plate Size	140 x 110mm
Bolt Hole Spacing	110x75mm
Plate Hole	23 x 13mm
Offset	48mm
Swivel Interference	376mm
Overall Height	198mm
Swivel Radius	188mm
Hardness Of Tread	92±5° Shore A
Load Capacity (Dynamic)	
Load Capacity (Static)	

Temperature

Fork Type

-20°C to +70°C


Swivel Caster With Front Brake

Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	6.45kgs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.