1147 Universal (Single) Spring Wheel Series

EQPU (brown arc) Wheel Diameter x Wheel Width 150 x 42mm


EAN

KS-11470600552211

Swivel Spring-loaded Caster with Welded Caster Fork
Blue painted finish, Mounting Type - Top Plate, 110x75 Bolt Hole Spacing
Cast Iron core with High Quality Polyurethane Wheel Tread
Cast Iron brown, Bearing – Ball Bearings

Wheel tread: Made of high-quality polyurethane Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 6 "

Wheel Width 1-11/16 "

Wheel Bearing Wheels With Ball Bearings

Plate Size 5-9/16 " x 4-3/8 "

Bolt Hole Spacing 4-5/16 " x3"

Plate Hole 15/16 " x 9/16 "

Offset 1-15/16 "

Swivel Interference 10 "

Overall Height 7-15/16 "

Swivel Radius 5 "

Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 1213lbs

Load Capacity (Static) 1819lbs

Temperature -4°F to +158°F

Fork Type Swivel Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 10.8lbs

Standard ISO22883

Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation

• • • • •

Dimensions







^{*} For any deviation between metric and imperial spec, please refer to the metric spec.