



1152 Anti-Friction Caster (B Type) Series

EQPU (brown round) Wheel Diameter x Wheel Width 125 x 40mm


EAN

KS-11520500552061

Swivel Caster with Welded Caster Fork and blue paint finish. Mounting Type - Top Plate, 129x74 Bolt Hole Spacing. Cast Iron Wheel Center with High Quality Polyurethane tread, Cast Iron brown. Bearing—Ball Bearing.

Wheel tread: Made of high-quality polyurethane
Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter	125mm
Wheel Width	86mm
Wheel Bearing	Wheels With Ball Bearings
Plate Size	114 x 159mm
Bolt Hole Spacing	129.4 x 73.8mm
Plate Hole	13 x 25.5mm
Offset	45mm
Swivel Interference	238mm
Overall Height	166mm
Swivel Radius	119mm
Hardness Of Tread	94±5° Shore A
Load Capacity (Dynamic)	1206kgs
Load Capacity (Static)	1809kgs
Temperature	-20°C to +80°C
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	6.46kgs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ○
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.