

DERSHENG
Dersheng Casters Keep Rolling

EAN

KS-11520600332741



A 3D model of a castor assembly. It features a blue square mounting plate with four pre-drilled holes for screws. A blue arm is attached to the bottom center of the plate, and a red wheel with a silver-colored metal hub is mounted at the end of this arm. A small black pin or screw is visible where the arm meets the wheel hub.

Wheel Center: iron core/cast iron core

Picture may differ from original product

Advantages at a glance

Wheel Diameter 6"

Wheel Bearing Wheels With Ball Bearings

Bolt Hole Spacing 4-5/16" x3"

Plate Hole 7/8" x 9/16"

Offset 1-11/16"

Swivel Interference 9-1/2"

Overall Height 7-7/8 "

Swivel Radius 4-3/4 "

Hardness Of Tread 93±5° Shore A

Load Capacity (Dynamic)	904lbs
-------------------------	--------

Load Capacity (Static)	1356lbs
------------------------	---------

Temperature -4°F to +158°F

Fork Type Swivel Caster

Stainless	N/A
-----------	-----

Electrical Conductivity	N/A
-------------------------	-----

Anti-Static	N/A
-------------	-----

Weight 9.8lbs

Standard ISO22883

Operating Noise ● ● ● ● ○

Floor Surface Preservation ● ● ● ● ○

Technical drawing of the 150mm castor wheel assembly, showing front and side views with dimensions:

- Front View (Left): Shows the wheel with a diameter of $\varnothing 150$ mm. The mounting plate has a width of 42 mm. The total height of the assembly is 197 mm.
- Side View (Right): Shows the profile of the wheel and the mounting plate. The width of the mounting plate is 42 mm.

© Copyright 2025 DershengInternational www.dersheng.com