1152 Anti-Friction Caster (B Type) Series

Dersheng Casters Keep Rolling

QPU (Brown round) Wheel Diameter × Wheel Width 150 x 42mm


EAN

KS-11520600531331

Rigid Caster with Welded Caster Fork, blue-painted finish. Mounting Type - Top Plate, 140x105mm Bolt Hole Spacing. Cast Iron Wheel Center with High Quality Polyurethane tread, Cast Iron brown. Bearing—Ball Bearing.

Wheel tread: Made of high-quality polyurethane Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 6 "

Wheel Width 4-1/2 "

Wheel Bearing Wheels With Ball Bearings

Plate Size 7 " x 5-9/16 "

Bolt Hole Spacing 5-1/2"x4-1/8"

Plate Hole 5/8 "

Overall Height 8-1/2 "

Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 2183lbs

Load Capacity (Dynamic)

Load Capacity (Static)

Temperature

-4°F to +158°F

Fork Type

Rigid Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 17.2lbs

Standard ISO22883

Advantages at a glance


Rolling Resistance

Operating Noise


• •

Floor Surface Preservation • • • • •

Dimensions



Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.