1152 Anti-Friction Caster Series

Dersheng Casters Keep Rolling

VQPU (brown round) Wheel Diameter x Wheel Width 300 x 90mm

EAN


KS-11521200544041

Rear Brake Locking system, Welded Caster Fork Blue-painted finish, Mounting Type - Top Plate, 140x85 Bolt Hole Spacing Cast Iron Wheel Center, High Quality Polyurethane tread, Cast Iron brown Bearing—precision bevel ball bearings

Wheel tread: Made of high-quality polyurethane

Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Metric ○ Imperial

Wheel Diameter 305mm
Wheel Width 90mm

Wheel Bearing Wheels With Ball Bearings

Plate Size 167 x 130mm **Bolt Hole Spacing** 140x85mm Plate Hole 22 x 13mm Offset 80mm Swivel Interference 474mm Overall Height 352mm **Swivel Radius** 237mm Hardness Of Tread 92±5° Shore A Load Capacity (Dynamic) 2250kgs Load Capacity (Static) 3375kgs Temperature -20°C to +70°C

Fork Type Swivel Caster With Rear Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 27.30kgs

Standard ISO22883

Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation

• • • • •

Dimensions



Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.