## 1155 STAT Series Caster Series (All Plastic)

Dersheng Casters Keep Rolling

Resolute (blue gray) Wheel Diameter × Wheel Width 100 x 31mm

**EAN** 


KS-11550400456053

Casters with a Total Brake and With locking system. Threaded Stem lock with blue-gray finish

Polyamide Fork—M12x25 thread, zinc-plated finish, Mounting Type - Threaded Stem. High-Quality Impact-Resistant Polypropylene Wheel Center with High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread. Dark gray, Bearing—Ball Bearings.

Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

## **Technical Data**

● Imperial ○ Metric

Wheel Diameter 4 "
Wheel Width 1-1/4 "

Wheel Bearing Wheels With Ball Bearings

Threaded Stem M12

Threaded Size 1"

Offset 1-7/16"

Swivel Interference 9"

Overall Height 5-1/2"

Swivel Radius 4-1/2"

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 198lbs

Load Capacity (Static) 298lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Total Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.2lbs


Standard ISO22881


## Advantages at a glance

Rolling Resistance
Operating Noise


Floor Surface Preservation • • • • •

## **Dimensions**





Mounting



<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.