1155 STAT Series Caster Series (All Plastic)

PPR (Blue Grey Dark Grey Plain Bearing Hub Lenth 37) Wheel diameter x Wheel width 100 x 24mm

EAN

KS-11550402266173

Double-locking Caster system, Threaded Stem M12x25 Blue-gray legs made of polyamide reinforcement, Threaded Stem installation Rust-proof, Corrosion resistant, Attractive appearance, Economical, and Smooth


High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread

Dark gray, Plain Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter Wheel Width

Wheel Bearing Wheel With Plain Bearing

Threaded Stem M12 Threaded Length 1-7/16 " Offset Swivel Interference 5-1/2 " Overall Height 4-1/2 " **Swivel Radius** Hardness Of Tread

85±5° Shore A

Load Capacity (Dynamic) 132lbs Load Capacity (Static) 198lbs

-4°F to +176°F Temperature


Fork Type Swivel Caster With Total Brake


Stainless N/A **Electrical Conductivity** N/A Anti-Static N/A Weight 1.4lbs ISO22883 Standard

Advantages at a glance


Rolling Resistance **Operating Noise** Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.