1155 STAT Series Caster Series (All Plastic)

Resolute (blue gray dark gray Plain Bearing Hub Lenth 35) Wheel Diameter x Wheel Width 125 x 31mm

EAN


KS-11550500458243

Long double-brake type, With locking system Casters, pin rivet—Ø28x30L Blue-gray legs made of polyamide reinforcement, pin-mounted installation Rust-proof, Corrosion resistant, Attractive appearance, Economical, and Smooth

High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread Dark gray, wheels—Plain Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR) Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

Metric O Imperial

Wheel Diameter 125mm Wheel Width 31.5mm

Wheel Bearing Wheel With Plain Bearing

Stem Diameter 28mm Stem Length 30mm Offset 38mm **Swivel Interference** 226mm 163mm **Overall Height Swivel Radius** 113mm

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 100kgs Load Capacity (Static) 150kgs

-20°C to +60°C Temperature


Fork Type Swivel Caster With Total Brake

Stainless N/A **Electrical Conductivity** N/A Anti-Static N/A Weight 0.97kgs ISO22881 Standard


Advantages at a glance

Rolling Resistance **Operating Noise** Floor Surface Preservation • • • • •

Dimensions



Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.