# 1155 STAT Series Caster Series (All Plastic)

PPR Wheel (Pearl Deep Grey - Plain Bearing Hub Lenth 35) Wheel Diameter x Wheel Width 125 x 24.5m

EAN

KS-11550502264113

Casters with a long double-With locking system, high-grade Top Plate—75x45 angled hole Top Plate

Pearlescent legs made of polyamide reinforcement, Mounting Type - Top Plate Rust-proof, Corrosion resistant, Attractive appearance, Economical, and Smooth


High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread

Dark gray, wheels—Plain Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

#### Technical Data

● Imperial ○ Metric

5 " Wheel Diameter

Wheel Width

Wheel Bearing Wheel With Plain Bearing

3-7/8 " x 2-3/4 " Plate Size

3" x 1-13/16" Bolt Hole Spacing

3/8 " x 3/8 " Plate Hole

1-1/2 " Offset

Swivel Interference

6-9/16 " Overall Height 4-1/2 " **Swivel Radius** 

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 154lbs

231lbs Load Capacity (Static)

Temperature -4°F to +140°F

Fork Type Swivel Caster With Total Brake

ISO22881

Stainless N/A **Electrical Conductivity** N/A Anti-Static N/A Weight 1.8lbs

Standard

Dersheng Casters Keep Rolling


#### Advantages at a glance

Rolling Resistance


**Operating Noise** 

Floor Surface Preservation • • • • •

### Dimensions



## Mounting



<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.