# 1155 STAT Series Caster Series (All Plastic)

PPR Wheel (Pearl Deep Grey - Plain Bearing Hub Lenth 35) Wheel Diameter x Wheel Width 125 x 24.5m

EAN

KS-11550502269133


Long double-brake type, With locking system Casters, hollow rivets—hollow 12-hole Pearl-colored legs made of polyamide reinforcement, locking installation Rust-proof, Corrosion resistant, Attractive appearance, Economical, and Smooth rotation

High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread

Dark gray, wheels—Plain Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

#### Technical Data

Metric O Imperial

Wheel Diameter 125mm
Wheel Width 24.5mm

Wheel Bearing Wheel With Plain Bearing

Single Bolt HoleCentre Hole 12.2mm

Offset 38mm

Swivel Interference 226mm

Overall Height 163mm

Swivel Radius 113mm

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 70kgs

Load Capacity (Static) 105kgs

Temperature -20°C to +60°C

Fork Type Swivel Caster With Total Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.77kgs

Standard ISO22881

#### Advantages at a glance

Rolling Resistance


 $\bullet$   $\bullet$   $\bullet$   $\circ$ 


Operating Noise

• • • 0


Floor Surface Preservation • • • • •

### Dimensions





## Mounting



 $<sup>\</sup>boldsymbol{\ast}$  For any deviation between metric and imperial spec, please refer to the metric spec.