1155 STAT Series Caster Series (All Plastic)

PPR (Blue Grey Dark Grey Plain Bearing Hub Lenth37) Wheel Diameter x Wheel Width 125 x 24.5mm

EAN

KS-11550502269173

Long double-brake type, With locking system Casters, hollow rivets—12 hollow holes Blue-gray legs made of polyamide reinforcement, locking installation Rust-proof, Corrosion resistant, Attractive appearance, Economical, and Smooth rotation


High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread

Dark gray, wheels—Plain Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 4 "
Wheel Width 1-1/4 "

Wheel Bearing Wheel With Plain Bearing

1/2 "

Single Bolt HoleCentre Hole

Offset 1-7/16 "

Swivel Interference 9 "

Overall Height 6-1/2 "

Swivel Radius 4-1/2 "

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 154lbs

Load Capacity (Static) 231lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Total Brake

ISO22881

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.7lbs

Standard


Advantages at a glance

Rolling Resistance


Operating Noise • • • • •

Floor Surface Preservation • • • • •

Dimensions



Mounting



 $[\]boldsymbol{\ast}$ For any deviation between metric and imperial spec, please refer to the metric spec.