



1155-1 Light Plastic-1 Series

PPR (Black Black - Plain Bearing Hub Lenth 37) Wheel Diameter x Wheel Width 125 x 31mm


EAN

KS-11550593265113

Actual Casters, Threaded Stem M12x25  
Black Casters with polyamide reinforcement, Threaded Stem installation  
Rust-proof, Corrosion resistant, Attractive appearance, Economical, and Smooth rotation  
High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread  
Black, Plain Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)  
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                          |
|------------------------------------------------------------------------|--------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                          |
| Wheel Diameter                                                         | 125mm                    |
| Wheel Width                                                            | 31mm                     |
| Wheel Bearing                                                          | Wheel With Plain Bearing |
| Threaded Stem                                                          | M12                      |
| Threaded Length                                                        | 25mm                     |
| Offset                                                                 | 38mm                     |
| Swivel Interference                                                    | 201mm                    |
| Overall Height                                                         | 164mm                    |
| Swivel Radius                                                          | 100.5mm                  |
| Hardness Of Tread                                                      | 82±5° Shore A            |
| Load Capacity (Dynamic)                                                | 90kgs                    |
| Load Capacity (Static)                                                 | 135kgs                   |
| Temperature                                                            | -20°C to +60°C           |
| Fork Type                                                              | Swivel Caster            |
| Stainless                                                              | N/A                      |
| Electrical Conductivity                                                | N/A                      |
| Anti-Static                                                            | N/A                      |
| Weight                                                                 | 0.56kgs                  |
| Standard                                                               | ISO22883                 |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.