



1157 57 Series Caster Series

PU (red round) Wheel Diameter x Wheel Width 125 x 40mm


EAN

KS-11570500332151

Swivel Caster with Welded Caster Fork, red painted finish.  
Mounting Type - Top Plate, 110x75 Bolt Hole Spacing.  
Cast Iron Wheel Center with High Quality Polyurethane Wheel Tread, Cast Iron red.  
Bearings—Ball Bearings.

Wheel tread: Made of high-quality polyurethane  
Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                           |
| Wheel Diameter                                                         | 5 "                       |
| Wheel Width                                                            | 1-5/8 "                   |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Plate Size                                                             | 5-9/16 " x 4-3/8 "        |
| Bolt Hole Spacing                                                      | 4-5/16 " x3"              |
| Plate Hole                                                             | 7/8 " x 9/16 "            |
| Offset                                                                 | 1-11/16 "                 |
| Swivel Interference                                                    | 8-1/2 "                   |
| Overall Height                                                         | 6-13/16 "                 |
| Swivel Radius                                                          | 4-1/4 "                   |
| Hardness Of Tread                                                      | 93±5° Shore A             |
| Load Capacity (Dynamic)                                                | 750lbs                    |
| Load Capacity (Static)                                                 | 1124lbs                   |
| Temperature                                                            | -4°F to +158°F            |
| Fork Type                                                              | Swivel Caster             |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 7.6lbs                    |
| Standard                                                               | ISO22883                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ○ ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ○ |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.