

1157 57 Series Caster Series

Non-marking NBR Rubber (milling) Wheel Diameter x Wheel Width 200 x 44mm


EAN

KS-11570800041071

Rigid Caster, Welded Caster Fork
 Red painted finish, Mounting Type - Top Plate, 85x70 Bolt Hole Spacing
 Cast Iron core, High-Quality, highly Resilient Rubber Wheel Tread, Cast Iron in natural color
 Bearings—Ball Bearings

Wheel surface: Made of high-quality, highly elastic rubber
 Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data


 Metric Imperial

| | |
|-------------------------|---------------------------|
| Wheel Diameter | 200mm |
| Wheel Width | 44mm |
| Wheel Bearing | Wheels With Ball Bearings |
| Plate Size | 100 x 115mm |
| Bolt Hole Spacing | 85 x 70mm |
| Plate Hole | 20 x 11mm |
| Overall Height | 240mm |
| Hardness Of Tread | 85±5° Shore A |
| Load Capacity (Dynamic) | 350kgs |
| Load Capacity (Static) | 525kgs |
| Temperature | -20°C to +80°C |
| Fork Type | Rigid Caster |
| Stainless | N/A |
| Electrical Conductivity | N/A |
| Anti-Static | N/A |
| Weight | 4.35kgs |
| Standard | ISO22883 |


Advantages at a glance

| | |
|----------------------------|-----------|
| Rolling Resistance | ● ● ● ○ ○ |
| Operating Noise | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ○ |

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 Dersheng International www.dersheng.com