

1165-3 AMR/AGV-3 Double Precision Ball Bearing Caster (Medium Duty) Series



QPU (blue round) Wheel Diameter x Wheel Width 62.5 x 45mm


EAN

KS-11655203532043

Swivel Caster, Welded Caster Fork, Zine-Plated finish  
Mounting Type - Top Plate, 75x45 Bolt Hole Spacing  
Cast Iron core, High Quality Polyurethane Wheel Tread  
Blue finish, Bearing—Ball Bearings

Wheel tread: Made of high-quality polyurethane  
Wheel Center: iron core/cast iron

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                           |
| Wheel Diameter                                                         | 2-1/2 "                   |
| Wheel Width                                                            | 1-13/16 "                 |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Plate Size                                                             | 3-11/16 " x 2-7/16 "      |
| Bolt Hole Spacing                                                      | 3 " x 1-13/16 "           |
| Plate Hole                                                             | 3/8 " x 3/8 "             |
| Offset                                                                 | 1-5/16 "                  |
| Swivel Interference                                                    | 5-3/16 "                  |
| Overall Height                                                         | 3-1/2 "                   |
| Swivel Radius                                                          | 2-9/16 "                  |
| Hardness Of Tread                                                      | 87±5° Shore A             |
| Load Capacity (Dynamic)                                                | 441lbs                    |
| Load Capacity (Static)                                                 | 661lbs                    |
| Temperature                                                            | -4°F to +158°F            |
| Fork Type                                                              | Swivel Caster             |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 1.9lbs                    |
| Standard                                                               | ISO22883                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ● ● ● |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.