

WPPR Series

WPPR Conductive Wheel (Black & Light Gray) Wheel Diameter x Wheel Width
100x50mm

EAN

KS-1202170420W177A

Easy to protect floors, Non-Marking, Easy To Maneuver, and capable of handling heavy loads. Low rolling and Swivel Resistance, Resistant To many other aggressive substances.. Color: Black and light gray



Wheel core: Made of high-quality impact-resistant polypropylene
Wheel tread: Thermoplastic rubber elastomer (TPR)
Bearing: precision ball

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

Metric Imperial

Wheel Diameter(D) 100mm

Wheel Width(T2) 50mm

Wheel Bearing Annular Ball Bearing

Axle Bore(d) 30.2mm

Axle Bore(S) —

Bearing Bore Depth(t) —

Hub Length(T1) 62mm

Hardness Of Tread 87±5° Shore A

Load Capacity (Dynamic) 136kgs

Load Capacity (Static) 204kgs

Temperature -20°C to +60°C

Electrical Conductivity $\times 10^3/\sim 10^4/\Omega$

Anti-Static N/A

Weight 0.40kgs

Standard ISO22883

Advantages at a glance

Rolling Resistance • • • • ○

Operating Noise • • • • ○

Floor Surface Preservation • • • • ○

2D Dimensional Drawing of Single Wheel

* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 Dersheng International www.dersheng.com