

WPPR Series

WPPR Conductive Wheel (Black & Light Gray) Wheel Diameter x Wheel Width
100x50mm

EAN

KS-1202170420W177A

Easy to protect floors, Non-Marking, Easy To Maneuver, and capable of handling heavy loads. Low rolling and Swivel Resistance, Resistant To many other aggressive substances.. Color: Black and light gray



Wheel core: Made of high-quality impact-resistant polypropylene
Wheel tread: Thermoplastic rubber elastomer (TPR)
Bearing: precision ball

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

Imperial Metric

Wheel Diameter(D) 4 "

Wheel Width(T2) 2 "

Wheel Bearing Annular Ball Bearing

Axle Bore(d) 1-3/16 "

Axle Bore(S) —

Bearing Bore Depth(t) —

Hub Length(T1) 2-1/2 "

Hardness Of Tread 87±5° Shore A

Load Capacity (Dynamic) 300lbs

Load Capacity (Static) 450lbs

Temperature -4°F to +140°F

Electrical Conductivity Y 10^3/~10^4/Ω

Anti-Static N/A

Weight 0.9lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance • • • • ○

Operating Noise • • • • ○

Floor Surface Preservation • • • • ○

2D Dimensional Drawing of Single Wheel

* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 Dersheng International www.dersheng.com