

## WPPR Series

WPPR Wheel (Pearlescent Light Gray) Wheel Diameter x Wheel Width 202 x 50mm

A

KS-1202260820W173

Easy to protect floors, Non-Marking, Easy To Maneuver, and capable of handling heavy loads. Low rolling and Swivel Resistance, Resistant To many other aggressive substances.. Color: Pearlescent light gray, with a Plain Bearing.



Wheel Tread: High-quality impact-resistant polypropylene  
 Wheel Center: Thermoplastic rubber elastomer (TPR)  
 Bearing: Long ball bearing

Drawings are for reference only and may differ from the product

Picture may differ from original product

## Technical Data

 Metric  Imperial

Wheel Diameter(D) 202mm

Wheel Width(T2) 50mm

Wheel Bearing Annular Ball Bearing

Axe Bore(d) 12.2mm

Axe Bore(S) —

Bearing Bore Depth(t) —

Hub Lenth(T1) 56mm

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 280kgs

Load Capacity (Static) 420kgs

Temperature -20°C to +60°C

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.80kgs

Standard ISO22883

## Advantages at a glance

Rolling Resistance • • • • ○

Operating Noise • • • • ○

Floor Surface Preservation • • • • ●

## 2D Dimensional Drawing of Single Wheel

\* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 DershengInternational www.dersheng.com