## **Product Data Sheet**

## **PPR Series**

Dersheng Casters Keep

PPR Wheel (Gray & Dark Gray) - Wheel Diameter × Wheel Width: 38x24mm


EAN

KS-12022651103172

Easy to protect floors, Non-Marking, Easy To Maneuver, and capable of handling heavy loads Low rolling and Swivel Resistance, Resistant To many other aggressive substances. Color: Dark gray, with Dust Cap

Wheel Tread: High-quality impact-resistant polypropylene Wheel Center: Thermoplastic rubber elastomer (TPR) Bearing: ball bearing

Drawings are for reference only and may differ from the product



Picture may differ from original product

## Technical Data

| _ |        | _          |          |
|---|--------|------------|----------|
|   | Metric | $\bigcirc$ | Imperial |

Wheel Diameter(D) 38mm
Wheel Width(T2) 24mm

Wheel Bearing Ball Bearing

Axle Bore(d) 6mm

Axle Bore(S) —

Bearing Bore Depth(t) —

Hub Lenth(T1) 25mm

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 30kgs

Load Capacity (Static) 45kgs

Temperature -20°C to +60°C

Electrical Conductivity

Anti-Static

N/A

Weight

0.05kgs

Standard

ISO22883

## Advantages at a glance

Rolling Resistance

Operating Noise

Floor Surface Preservation

• • • • •

2D Dimensional Drawing of Single Wheel

<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.