

PP Series

PP Wheel (Black-Black) Wheel Diameter x Wheel Width 50 x 45mm

D

KS-12022902181400



Good Heat Resistance, Rigid yet tough, fatigue-resistant, and stress-cracking resistant.
Unaffected by humidity, resistant to corrosion, oil, acids, alkalis, and other solvents.
Odorless and recyclable, with Heavy Load and low Rolling Resistance.
Color: Black

Wheel Center: High-quality impact-resistant polypropylene
Wheel Tread: High-quality impact-resistant polypropylene
Bearing: No center tube

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

 Metric Imperial

Wheel Diameter(D) 50mm

Wheel Width(T2) 45mm

Wheel Bearing Plain Bearing

Axe Bore(d) —

Axe Bore(S) 10mm

Bearing Bore Depth(t) —

Hub Lenth(T1) 49mm

Hardness Of Tread 65±5° Shore D

Load Capacity (Dynamic) 50kgs

Load Capacity (Static) 75kgs

Temperature -10°C to +60°C

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.02kgs

Standard ISO22883


Advantages at a glance

Rolling Resistance • • • •

Operating Noise • • • ○ ○

Floor Surface Preservation • • • ○ ○

2D Dimensional Drawing of Single Wheel



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2026 DershengInternational www.dersheng.com