

PP Series

PP Wheel (Black) Wheel Diameter x Wheel Width 75x45mm

EAN

KS-12022903181400



Non-marking, quiet, and equipped with wheel covers.
 High-Quality wheels manufactured using injection molding.

Wheel core: Made of high-quality impact-resistant polypropylene
 Wheel tread: Thermoplastic rubber elastomer (TPR)
 Bearing: precision ball

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

 Imperial Metric

Wheel Diameter(D)

3 "

Wheel Width(T2)

1-13/16 "

Wheel Bearing

Plain Bearing

Axe Bore(d)

3/8 "

Axe Bore(S)

—

Bearing Bore Depth(t)

—

Hub Lenth(T1)

2 "

Hardness Of Tread

65±5° Shore D

Load Capacity (Dynamic)

154lbs

Load Capacity (Static)

231lbs

Temperature

14°F to +140°F

Electrical Conductivity

N/A

Anti-Static

N/A

Weight

0.4lbs

Standard

ISO22883

Advantages at a glance

Rolling Resistance Operating Noise Floor Surface Preservation

2D Dimensional Drawing of Single Wheel

* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 DershengInternational www.dersheng.com