



Resolute Rubber Wheel Series

All-Purpose Wheel (White/Black) Wheel Diameter × Wheel Width 50×20mm

EAN

KS-12024502083173

Easy to protect floors, Non-Marking, Easy To Maneuver, and capable of handling heavy loads
Low rolling and Swivel Resistance, Resistant To many other aggressive substances.
Colors: White and Black

Wheel Tread: High-quality impact-resistant polypropylene
Wheel Center: Thermoplastic rubber elastomer (TPR)
Bearing: ball bearing

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter(D)	50mm
Wheel Width(T2)	20mm
Wheel Bearing	Ball Bearing
Axle Bore(d)	6mm
Axle Bore(S)	—
Bearing Bore Depth(t)	—
Hub Lenth(T1)	26mm
Hardness Of Tread	72±5° Shore A
Load Capacity (Dynamic)	56kgs
Load Capacity (Static)	84kgs
Temperature	-20°C to +60°C
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.02kgs
Standard	ISO22883

Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

2D Dimensional Drawing of Single Wheel

* For any deviation between metric and imperial spec, please refer to the metric spec.