


Resolute Rubber Wheel Series

Resolute(Gray Light Gray Arc) Wheel Diameter×Wheel Width 100×50mm

EAN

KS-12024504208174

Easy to Floor Surface Preservation, Non-Markings, Easy To Maneuver, and can withstand heavy loads.
 Low rolling and Swivel Resistance, resistant to corrosion from many corrosive substances.
 Color: Light gray



Wheel core: Made of high-quality impact-resistant polypropylene
 Wheel tread: Thermoplastic rubber elastomer (TPR)
 Bearing: Precision ball bearing

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

 Imperial Metric

Wheel Diameter(D) 4 "

Wheel Width(T2) 2 "

Wheel Bearing Annular Ball Bearing

Axe Bore(d) 1/2 "

Axe Bore(S) —

Bearing Bore Depth(t) —

Hub Lenth(T1) 2-1/2 "

Hardness Of Tread 72±5° Shore A

Load Capacity (Dynamic) 300lbs

Load Capacity (Static) 450lbs

Temperature -4°F to +140°F

Electrical Conductivity N/A

Anti-Static N/A


Weight 1.0lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance	• • • •
Operating Noise	• • • •
Floor Surface Preservation	• • • •

2D Dimensional Drawing of Single Wheel



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 DershengInternational www.dersheng.com