



Resolute Rubber Wheel Series

All-Purpose Wheel (Pearlescent Dark Gray, Flat) Wheel Diameter × Wheel Width  
40.5×22mm

EAN

KS-12024561100171

Easy to protect floors, Non-Marking, Easy To Maneuver, and capable of handling heavy loads Low rolling and Swivel Resistance, Resistant To many other aggressive substances. Color: Pearlescent dark gray, with Dust Cap

Wheel Tread: High-quality impact-resistant polypropylene  
Wheel Center: Thermoplastic rubber elastomer (TPR)  
Bearing: ball bearing

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

|                                                                        |                |
|------------------------------------------------------------------------|----------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                |
| Wheel Diameter(D)                                                      | 40.5mm         |
| Wheel Width(T2)                                                        | 22mm           |
|                                                                        |                |
| Wheel Bearing                                                          | Ball Bearing   |
| Axle Bore(d)                                                           | 6mm            |
| Axle Bore(S)                                                           | —              |
| Bearing Bore Depth(t)                                                  | —              |
| Hub Lenth(T1)                                                          | 25.5mm         |
| Hardness Of Tread                                                      | 82±5° Shore A  |
| Load Capacity (Dynamic)                                                | 56kgs          |
| Load Capacity (Static)                                                 | 84kgs          |
| Temperature                                                            | -20°C to +60°C |
| Electrical Conductivity                                                | N/A            |
| Anti-Static                                                            | N/A            |
| Weight                                                                 | 0.04kgs        |
| Standard                                                               | ISO22883       |

Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ● |

2D Dimensional Drawing of Single Wheel

\* For any deviation between metric and imperial spec, please refer to the metric spec.