# 1106 Medical Caster Series

Dersheng Casters Keep Rolling

PPR Wheel Diameter × Wheel Width 75 x 31mm

EAN

TW-4110603001003

Rigid Caster with integral Stamping bracket and angled hole. Zine-Plated, Mounting Type - Top Plate. High-Quality Impact-Resistant Polypropylene core with High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread. Dark gray. Ball Bearing bearings.

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

### Technical Data

Wheel Width

● Metric ○ Imperial

Wheel Diameter 75mm

Wheel Bearing Wheels With Ball Bearings

31mm

Plate Size 92 x 70mm

Bolt Hole Spacing 74.5 x 49mm

Plate Hole 15 x 10mm

Overall Height 113.5mm

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 70kgs

Load Capacity (Static) 105kgs

Temperature -20°C to +60°C

Fork Type Rigid Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.40kgs

Standard ISO22883

### Advantages at a glance

Rolling Resistance


 $\bullet$   $\bullet$   $\bullet$   $\circ$ 

Operating Noise


• • • 0

Floor Surface Preservation • • • • •

#### **Dimensions**



## Mounting



<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.