



1112 2" Wide General Purposes Caster Series


Rubber (black) Wheel Diameter × Wheel Width 202 x 50mm

EAN  
TW-4111208002007

Swivel Caster with Welded Caster Fork Zine-Plated, Mounting Type - Top Plate Cast Iron  
Wheel Center with High-Quality Resilient Rubber tread Black, Bearing—Annual Ball Bearing.

Wheel Tread: high-quality elastic rubber  
Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                                |
|------------------------------------------------------------------------|--------------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                                |
| Wheel Diameter                                                         | 202mm                          |
| Wheel Width                                                            | 50mm                           |
| Wheel Bearing                                                          | Wheel With Annual Ball Bearing |
| Plate Size                                                             | 135 x 110mm                    |
| Bolt Hole Spacing                                                      | 105 x 78mm                     |
| Plate Hole                                                             | 20 x 11mm                      |
| Offset                                                                 | 45mm                           |
| Swivel Interference                                                    | 290mm                          |
| Overall Height                                                         | 190mm                          |
| Swivel Radius                                                          | 145mm                          |
| Hardness Of Tread                                                      | 80±5° Shore A                  |
| Load Capacity (Dynamic)                                                | 300kgs                         |
| Load Capacity (Static)                                                 | 450kgs                         |
| Temperature                                                            | -20°C to +120°C                |
| Fork Type                                                              | Swivel Caster                  |
| Stainless                                                              | N/A                            |
| Electrical Conductivity                                                | N/A                            |
| Anti-Static                                                            | N/A                            |
| Weight                                                                 | 4.20kgs                        |
| Standard                                                               | ISO22883                       |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ○ ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ○ |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.