

## 1112 2" Wide General Purposes Caster Series

PU (green) Wheel Diameter x Wheel Width 200 x 49mm


EAN

TW-4111208004031

Equipped with front-brake locking Casters. Welded Caster Fork. Zinc-Plated, Mounting Type - Top Plate. Cast Iron wheel Wheel Hub, High Quality Polyurethane Wheel Tread. Green, Ball Bearings.

Wheel surface: High-quality polyurethane  
Wheel Center: Iron core/Cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

## Technical Data

 Metric  Imperial

Wheel Diameter 200mm

Wheel Width 49mm

Wheel Bearing Wheel With Annual Ball Bearing

Plate Size 115 x 100mm

Bolt Hole Spacing 85 x 70mm

Plate Hole 20 x 11mm

Offset 45mm

Swivel Interference 320mm

Overall Height 240mm

Swivel Radius 145mm

Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 420kgs

Load Capacity (Static) 630kgs

Temperature -20°C to +70°C

Fork Type Swivel Caster With Front Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 4.80kgs

Standard ISO22883


## Advantages at a glance

Rolling Resistance • • • ○ ○


Operating Noise • • • • ○

Floor Surface Preservation • • • • ○

## Dimensions



## Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 DershengInternational www.dersheng.com