


1116-SS-MJ Medium Duty Stainless Steel Caster Series

Nylon wheel (white) Wheel diameter x wheel width 125 x 38mm

EAN

TW-4111605001004

Rigid Casters, Stamping Fabricated Caster Fork; surface vibration, Mounting Type - Top Plate device; thermoplastic Wheel Center and Wheel Tread; white, wheel-Plain Bearing.



Wheel surface: thermoplastic
Wheel Center: thermoplastic

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

 Metric Imperial

Wheel Diameter 125mm

Wheel Width 38mm

Wheel Bearing Wheel With Plain Bearing

Plate Size 95 x 95mm

Bolt Hole Spacing 70 x 70mm

Plate Hole 13.5 x 10.5mm

Overall Height 160mm

Hardness Of Tread 75±5° Shore D

Load Capacity (Dynamic) 140kgs

Load Capacity (Static) 210kgs

Temperature -20°C to +80°C

Fork Type Rigid Caster

Stainless Y

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.55kgs

Standard ISO22883


Advantages at a glance

Rolling Resistance • • • •


Operating Noise • • ○ ○ ○

Floor Surface Preservation • • ○ ○ ○

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 DershengInternational www.dersheng.com