

1116-SS-MJ Medium Duty Stainless Steel Caster Series




Nylon wheel (white) Wheel diameter × wheel width 125 x 38mm

EAN  
TW-4111605001004

Rigid Casters, Stamping Fabricated Caster Fork; surface vibration, Mounting Type - Top Plate device; thermoplastic Wheel Center and Wheel Tread; white, wheel-Plain Bearing.

Wheel surface: thermoplastic  
Wheel Center: thermoplastic

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                          |
|------------------------------------------------------------------------|--------------------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                          |
| Wheel Diameter                                                         | 5 "                      |
| Wheel Width                                                            | 1-1/2 "                  |
| Wheel Bearing                                                          | Wheel With Plain Bearing |
| Plate Size                                                             | 3-13/16 " x 3-13/16 "    |
| Bolt Hole Spacing                                                      | 2-3/4 " x 2-3/4 "        |
| Plate Hole                                                             | 9/16 " x 3/8 "           |
| Overall Height                                                         | 6-3/8 "                  |
| Hardness Of Tread                                                      | 75±5° Shore D            |
| Load Capacity (Dynamic)                                                | 309lbs                   |
| Load Capacity (Static)                                                 | 463lbs                   |
| Temperature                                                            | -4°F to +176°F           |
| Fork Type                                                              | Rigid Caster             |
| Stainless                                                              | Y                        |
| Electrical Conductivity                                                | N/A                      |
| Anti-Static                                                            | N/A                      |
| Weight                                                                 | 1.2lbs                   |
| Standard                                                               | ISO22883                 |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ○ ○ ○ |
| Floor Surface Preservation | ● ● ○ ○ ○ |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.