

# 1116-SS-MI Medium Duty Institutional Stainless Steel Caster Series




Nylon Wheel Diameter × Wheel Width 125 x 38mm

EAN  
TW-4111605002042

Swivel Casters, Threaded Stem Stamping Fork—1/2"-12 UNC; surface vibration protection, Mounting Type - Threaded Stem; thermoplastic Wheel Center and rim; white; Plain Bearings.

Wheel surface: thermoplastic  
Wheel Center: thermoplastic

Drawings are for reference only and may differ from the product



Picture may differ from original product

## Technical Data


Imperial  Metric

Wheel Diameter	5 "
Wheel Width	1-1/2 "
Wheel Bearing	Wheel With Plain Bearing
Threaded Stem	1/2 " -12
Threaded Length	1-1/8 "
Offset	1-9/16 "
Swivel Interference	8 "
Overall Height	6-7/16 "
Swivel Radius	4 "
Hardness Of Tread	75±5° Shore D
Load Capacity (Dynamic)	309lbs
Load Capacity (Static)	463lbs
Temperature	-4°F to +176°F
Fork Type	Swivel Caster
Stainless	Y
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	1.7lbs
Standard	ISO22883


## Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ○ ○ ○
Floor Surface Preservation	● ● ○ ○ ○

## Dimensions



## Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.