

# 1116-SS-MI Medium Duty Institutional Stainless Steel Caster Series



Nylon Wheel Diameter × Wheel Width 125 x 38mm

EAN


TW-4111605002053

Swivel Casters, Riveted and Stamping Top Plate brackets—high-grade perforations Surface vibration, Mounting Type - Top Plate device Reinforced Polypropylene and Wheel Tread White, Bearing—Ball Bearings.

Wheel surface: thermoplastic

Wheel Center: thermoplastic

Drawings are for reference only and may differ from the product



Picture may differ from original product

## Technical Data


Metric  Imperial

Wheel Diameter	125mm
Wheel Width	38mm
Wheel Bearing	Wheels With Ball Bearings
Plate Size	92 x 70mm
Bolt Hole Spacing	75 x 45mm
Plate Hole	12 x 9mm
Offset	39mm
Swivel Interference	203mm
Overall Height	163.5mm
Swivel Radius	101.5mm
Hardness Of Tread	75±5° Shore D
Load Capacity (Dynamic)	140kgs
Load Capacity (Static)	210kgs
Temperature	-20°C to +80°C
Fork Type	Swivel Caster
Stainless	Y
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.85kgs
Standard	ISO22883


## Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

## Dimensions



## Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.