



1129 Medical Caster Series


PPR Wheel Diameter × Wheel Width 75 x 31mm

EAN  
TW-4112903002013

Swivel Caster, Riveted Stamping Fork - 1/2-12 threads  
Zine-Plated, Mounting Type - Threaded Stem  
High-Quality Impact-Resistant Polypropylene core, High-Quality Reinforced Polypropylene  
Rubber (TPR) Wheel Tread  
Dark gray, Bearing - Ball Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR)  
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                           |
| Wheel Diameter                                                         | 75mm                      |
| Wheel Width                                                            | 31mm                      |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Threaded Stem                                                          | 1/2 " -12牙                |
| Threaded Size                                                          | 32mm                      |
| Offset                                                                 | 42.5mm                    |
| Swivel Interference                                                    | 160mm                     |
| Overall Height                                                         | 116mm                     |
| Swivel Radius                                                          | 80mm                      |
| Hardness Of Tread                                                      | 82±5° Shore A             |
| Load Capacity (Dynamic)                                                | 70kgs                     |
| Load Capacity (Static)                                                 | 105kgs                    |
| Temperature                                                            | -20°C to +60°C            |
| Fork Type                                                              | Swivel Caster             |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 0.50kgs                   |
| Standard                                                               | ISO22883                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.