



1129 Medical Caster Series


PPR (red) Wheel Diameter × Wheel Width 75 x 31mm

EAN
TW-4112903002026

Swivel Caster with Riveted Fork and Stamping Fork - round hole Zine-Plated, Top Plate (4T) Mounting Type system High-Quality Impact-Resistant Polypropylene core, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread Red color, Bearing - Ball Bearing.

Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Imperial ☐ Metric	
Wheel Diameter	3 "
Wheel Width	1-1/4 "
Wheel Bearing	Wheels With Ball Bearings
Plate Size	4-3/8 " x 3-11/16 "
Bolt Hole Spacing	3-7/16 " x 2-13/16 "
Plate Hole	25/64 "
Offset	1-11/16 "
Swivel Interference	6-3/8 "
Overall Height	4-1/2 "
Swivel Radius	3-3/16 "
Hardness Of Tread	82±5° Shore A
Load Capacity (Dynamic)	154lbs
Load Capacity (Static)	231lbs
Temperature	-4°F to +140°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	1.8lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.