1129 Medical Caster Series

Dersheng Casters Keep Rolling

PPR Wheel Diameter × Wheel Width 100 x 31mm

EAN

TW-4112904002015

Swivel Caster with Riveted Stamping Fork - 3/8-16 threads
Zine-Plated, Mounting Type - Threaded Stem
High-Quality Impact-Resistant Polypropylene core, High-Quality Reinforced Polypropylene
Rubber (TPR) Wheel Tread
Dark gray, wheel - Plain Bearing

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Metric ○ Imperial

Wheel Diameter 100mm
Wheel Width 31mm

Wheel Bearing Wheel With Plain Bearing

Threaded Stem 3/8"-16牙
Threaded Size 32mm
Offset 40mm
Swivel Interference 180mm
Overall Height 141mm
Swivel Radius 90mm

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 80kgs

Load Capacity (Static) 120kgs

Temperature -20°C to +60°C

Fork Type Swivel Caster

Stainless N/A

Electrical Conductivity

Anti-Static

N/A

Weight

0.55kgs

Standard

ISO22883

Advantages at a glance

Rolling Resistance


• • • • 0

Operating Noise


• • • • •

Floor Surface Preservation $\bullet \bullet \bullet \bullet \bullet$

Dimensions



Mounting



 $[\]boldsymbol{\ast}$ For any deviation between metric and imperial spec, please refer to the metric spec.