




1129 Medical Caster Series

Resolute Wheel Diameter × Wheel Width 100 x 31mm

EAN  
TW-4112904004038

Casters with Total Brakes and With locking system. Threaded Stem, Riveted Stamping Fork - 1/2-12 threads Zine-Plated, Mounting Type - Threaded Stem High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread Dark gray, Bearing - Ball Bearings



Picture may differ from original product

Wheel tread: Thermoplastic rubber elastomer (TPR)  
Wheel Center: high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product


Technical Data

|                                                                        |                                |
|------------------------------------------------------------------------|--------------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                                |
| Wheel Diameter                                                         | 100mm                          |
| Wheel Width                                                            | 31mm                           |
| Wheel Bearing                                                          | Wheels With Ball Bearings      |
| Threaded Stem                                                          | 1/2 " -12牙                     |
| Threaded Size                                                          | 32mm                           |
| Offset                                                                 | 40mm                           |
| Swivel Interference                                                    | 212mm                          |
| Overall Height                                                         | 141mm                          |
| Swivel Radius                                                          | 106mm                          |
| Hardness Of Tread                                                      | 72±5° Shore A                  |
| Load Capacity (Dynamic)                                                | 125kgs                         |
| Load Capacity (Static)                                                 | 187.5kgs                       |
| Temperature                                                            | -20°C to +60°C                 |
| Fork Type                                                              | Swivel Caster With Total Brake |
| Stainless                                                              | N/A                            |
| Electrical Conductivity                                                | N/A                            |
| Anti-Static                                                            | N/A                            |
| Weight                                                                 | 0.65kgs                        |
| Standard                                                               | ISO22883                       |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ● ● ● |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.