

1130 Medium Duty General Purposes Caster Series




PP Wheel Diameter × Wheel Width 75 x 32mm

EAN  
TW-4113003001013

Rigid Caster with Stamping Fabricated Caster Fork and 75 x 45 mm (3" x 1-3/4") Bolt Hole Spacing. Zine-Plated, Mounting Type - Top Plate. Polypropylene core and Wheel Tread. Black, Plain Bearing.

Wheel tread: PP polypropylene  
Wheel Center: PP polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                          |
|------------------------------------------------------------------------|--------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                          |
| Wheel Diameter                                                         | 75mm                     |
| Wheel Width                                                            | 32mm                     |
| Wheel Bearing                                                          | Wheel With Plain Bearing |
| Plate Size                                                             | 92 x 70mm                |
| Bolt Hole Spacing                                                      | 75X45mm                  |
| Plate Hole                                                             | 12 x 9mm                 |
| Offset                                                                 | 54mm                     |
| Swivel Interference                                                    | 260mm                    |
| Overall Height                                                         | 106mm                    |
| Swivel Radius                                                          | 60mm                     |
| Hardness Of Tread                                                      | 65±5° Shore D            |
| Load Capacity (Dynamic)                                                | 90kgs                    |
| Load Capacity (Static)                                                 | 135kgs                   |
| Temperature                                                            | -10°C to +60°C           |
| Fork Type                                                              | Rigid Caster             |
| Stainless                                                              | N/A                      |
| Electrical Conductivity                                                | N/A                      |
| Anti-Static                                                            | N/A                      |
| Weight                                                                 | 0.40kgs                  |
| Standard                                                               | ISO22883                 |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ● ○ ○ |
| Floor Surface Preservation | ● ● ● ○ ○ |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.